

Q8 Haydn 68

Application

- Wide range of hydraulic equipment

Specifications

- ISO 11158, category HM
- SS 155434, category AM
- DIN 51524 part 2, category HLP
- MAG IAS P-68, P-69, P-70
- Denison HF-0, HF-1 and HF-2
- AFNOR 48-603, category HM
- ISO 6743-4, category HM
- DIN 51502, category HLP
- Eaton Brochure 03-401-2010
- DIN 51517-2, category CL

Benefits

- Optimum anti-wear performance, based on a zincdiakylthiophosphate additive
- Long service life due to high thermal and oxidation stability for high temperature applications
- Trouble-free operation due to the unique combination of outstanding demulsibility, foam, air release, hydrolytic stability and filterability characteristics
- Can also be applied in other industrial equipment such as screw-air compressors and not severely loaded gears

Features and Benefits

- Optimum anti-wear performance, based on a zincdiakylthiophosphate additive
- Long service life due to high thermal and oxidation stability for high temperature applications
- Trouble-free operation due to the unique combination of outstanding demulsibility, foam, air release, hydrolytic stability and filterability characteristics
- Can also be applied in other industrial equipment such as screw-air compressors and not severely loaded gears

References

- Q8 Haydn meets the requirements of the major hydraulic component manufacturers.



| Properties | Method | Unit | Typical |
|------------------------------------|-----------|--------------------|-------------|
| ISO Viscosity Grade | - | - | 68 |
| Absolute Density, 15 °C | D 4052 | kg/m ³ | 880 |
| Kinematic Viscosity, 40 °C | D 445 | mm ² /s | 68.0 |
| Kinematic Viscosity, 100 °C | D 445 | mm ² /s | 8.66 |
| Viscosity Index | D 2270 | - | 97 |
| Flash Point | D 92 | °C | 246 |
| Pour Point | D 97 | °C | -30 |
| Copper Strip, 3 h, 100 °C | D 130 | - | 1 |
| Rust Test, Proc. A and B, 24 h | D 665 | - | pass |
| Total Acid Number | D 974 | mg KOH/g | 0.3 |
| Emulsion, Distilled Water, 54.4 °C | D 1401 | - | 40-40-0(15) |
| Air Release, 50 °C | DIN 51381 | min | 6 |
| Foam, 5 min blowing, seq. 1/2/3 | D 892 | ml | 5/10/5 |
| 10 min settling, seq. 1/2/3 | | ml | 0/0/0 |
| FZG Test, A/8.3/90 | DIN 51354 | load stage | 12 |
| Oxidation, Time to 2.0 TAN | D 943 | hours | >1500 |

The figures above are not a specification. They are typical figures obtained within production tolerances.

