

Q8 T 520 SAE 20

Monogrades

Description

Diesel engine lubricant also suitable for use in hydraulic systems and transmissions

Application

- In some diesel engines operating requiring SAE20 viscosity grade
- In transmission applications
- Also for hydraulic systems requiring high viscosity retention

Recommendations

- Q8 T 520 Monograde may be used as engine or transmission lubricant in commercial vehicles, buses, off-highway/construction or military equipment, when one or more of the following specifications are used to describe the required lubricant quality:

Specifications

- API CG-4

Benefits

- Universal mixed fleet engine lubricant
- Universal engine/transmission lubricant for buses and off-highway or military equipment
- Reduces handling and storage costs
- Prohibits use of wrong oil
- Prohibits corrosion and protects against rust

Properties	Method	Unit	Typical
Viscosity Grade			SAE 20W-20
Absolute Density, 15 °C	D 4052	g/ml	0.883
Kinematic Viscosity, 40 °C	D 445	mm ² /s	61.3
Kinematic Viscosity, 100 °C	D 445	mm ² /s	8.6
Viscosity Index	D 2270	-	114
Flash Point	D 93	°C	210
Pour Point	D 97	°C	-30
Total Base Number	D 2896	mg KOH/g	8.5
Sulphated Ash Content	D 874	% mass	1.1

The figures above are not a specification. They are typical figures obtained within production tolerances.

