

Product Data Sheet

Lithium Moly EP 23

A premium quality multi-purpose grease for use in all plain bearings subjected to high load conditions. The incorporation of molybdenum disulphide imparts a high degree of wear protection against load, shock loading and dusty environments. Used extensively for applications throughout industry and the automotive sector.

Features

- Excellent extreme pressure and anti-wear performance
- High degree of corrosion protection
- Highly versatile multi-purpose grease

Application

Lithium Moly EP 23 can be applied manually, or by using a standard grease gun (400gm cartridges available), or via a central lubricating system designed for and capable of pumping an NLGI No.2 grease; consult a qualified centralised lubrication systems engineer before installation.

As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge bearings prior to application. Likewise, as a general rule, take care not to over-lubricate and apply the quantity of grease recommended by the bearing manufacturer.

Properties	Specification	Results
Appearance	-	Smooth grease
Colour	-	Grey/black
NLGI classification	-	2
Thickener	-	Lithium soap
Base oil	-	Blended mineral oils
Worked penetration	IP50	265-295
Dropping point (°C)	IP132	185 min
Oil separation (%)	IP121	5 max
Copper corrosion	IP112	Pass
Resistance to corrosion Emcor (a)	IP 220	0:0
Water washout @ 39°C %	ASTM D1264	3
Four Ball Weld Load (kgs)	IP 239	315
Operating temperature range	-	-20°C to 140°C
Solids %	-	1

The information above is believed to be accurate and given in good faith but without warranty.

It is the users responsibility to determine the suitability of the product. (Feb 2014)