

# Q8 Chain Oil 150

## Application

- Chains and slides of chainsaws

## Specifications

- ISO 6743-1, category L-AC

## Benefits

- Low oil consumption and effective wear protection through strong adhesive oil film
- Suitable for use at low temperatures due to low pour points
- No harmful or unpleasant odours due to careful component selection

## References

- Q8 Chain Oil 150 is especially developed for the lubrication of chains and slides of chainsaws for a wide range of ambient temperatures.

| Properties                  | Method | Unit               | Typical |
|-----------------------------|--------|--------------------|---------|
| ISO Viscosity Grade         | -      | -                  | 150     |
| Absolute Density, 15 °C     | D 4052 | kg/m <sup>3</sup>  | 887     |
| Kinematic Viscosity, 40 °C  | D 445  | mm <sup>2</sup> /s | 150.0   |
| Kinematic Viscosity, 100 °C | D 445  | mm <sup>2</sup> /s | 14.60   |
| Viscosity Index             | D 2270 | -                  | 96      |
| Flash Point                 | D 92   | °C                 | 262     |
| Pour Point                  | D 97   | °C                 | -12     |
| Colour                      | D 1500 | -                  | L2.0    |
| Copper Strip, 3 h, 100 °C   | D 130  | -                  | 1       |
| Total Acid Number           | D 974  | mg KOH/g           | <0.05   |
| Texture                     | KPI 5  | -                  | stringy |

The figures above are not a specification. They are typical figures obtained within production tolerances.

