# Q8 Dynobear 220

## Description

Q8 Dynobear is a range of advanced multi-purpose lubricants specifically developed for the lubrication of machine tools, factory plant and machinery in general. They contain a special oiliness additive which reduces the friction. The oiliness additive eliminates stick-slip and judder that sometimes occurs in mechanically and hydraulically operated machine tools, this is achieved without the use of tackiness agents that can attract dust and abrasive particles and increase wear on exposed parts. Q8 Dynobears oils give outstanding low wear performance even in the hardest worked machinery.

## Application

- Q8 Dynobear range is recommended for all machine tools and general factory lubrication.
- Q8 Dynobear 220 is also recommended for medium duty gearboxes.

## Benefits

- Advanced multi purpose lubricants
- Eliminates stick-slip and judder
- Suitable for all machinery and machine tools
- Special oiliness additive which substantially reduces friction
- Outstanding rust protection

| Properties | Method | Unit | Typical |
|---|---|---|---|
| ISO Viscosity Grade | - | - | 220 |
| Absolute Density, 15 °C | D 4052 | kg/m³ | 891 |
| Kinematic Viscosity, 40 °C | D 445 | mm²/s | 220 |
| Kinematic Viscosity, 100 °C | D 445 | mm²/s | 18.9 |
| Viscosity Index | D 2270 | - | 96 |
| Flash Point | D 92 | °C | 284 |
| Colour | D 1500 | - | L2.0 |

*The figures above are not a specification. They are typical figures obtained within production tolerances.*



